

P&H 5170 履带式起重机主臂性能表

建议使用时查随车性能表

说明：暂缺少部分组件，带*号标示副臂工况不能组装

单位：吨

| 主臂长度 跨距 | 18m | 21m | 24m | 27m | 30m | 33m | 36m | 39m | 42m | 45m | 48m | 51m | 54m | 57m | 61m | 64m | 67m | 70m | 73m | 67m主+ | 67m主+ | 67m主+ | 70m主+ | 73m主+ | 主臂长度 跨距 | | |
|------------|-------|-------|-------|-------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|-------|-------|--------|--------|--------|------------|------------|-----|
| | 60' | 70' | 80' | 90' | 100' | 110' | 120' | 130' | 140' | 150' | 160' | 170' | 180' | 190' | 200' | 210' | 220' | 230' | 240' | 12m副 | 18m副 | * 24m副 | * 24m副 | * 24m副 | | | |
| 5m | 150.0 | | | | | | | | | | | | | | | | | | | | | | | | 5m | | |
| 6m | 140.0 | 128.1 | 116.8 | | | | | | | | | | | | | | | | | | | | | | | 6m | |
| 7m | 123.6 | 121.7 | 111.5 | 102.5 | 94.4 | | | | | | | | | | | | | | | | | | | | | 7m | |
| 8m | 99.1 | 98.8 | 98.7 | 96.2 | 90.7 | 83.8 | 77.8 | | | | | | | | | | | | | | | | | | | 8m | |
| 9m | 82.5 | 82.3 | 82.2 | 82.0 | 81.8 | 78.8 | 75.2 | 69.6 | | | | | | | | | | | | | | | | | | 9m | |
| 10m | 70.5 | 70.3 | 70.2 | 70.1 | 69.9 | 69.8 | 69.2 | 66.5 | 62.3 | 57.8 | | | | | | | | | | | | | | | | 10m | |
| 12m | 54.6 | 54.3 | 54.2 | 54.0 | 53.8 | 53.7 | 53.5 | 53.3 | 53.2 | 52.2 | 49.6 | 46.9 | 43.5 | 40.0 | | | | | | | | | | | | 12m | |
| 14m | 44.5 | 44.2 | 44.0 | 43.9 | 43.6 | 43.5 | 43.2 | 43.1 | 42.9 | 42.7 | 42.6 | 41.8 | 40.3 | 38.1 | 37.0 | 36.2 | 33.5 | 30.3 | | | | | | | | 14m | |
| 16m | 37.5 | 37.1 | 37.0 | 36.8 | 36.5 | 36.4 | 36.1 | 35.9 | 35.8 | 35.6 | 35.5 | 35.2 | 35.1 | 33.8 | 35.6 | 35.2 | 32.7 | 29.6 | 27.1 | | | | | | | 16m | |
| 18m | | 32.0 | 31.8 | 31.6 | 31.3 | 31.1 | 30.8 | 30.7 | 30.6 | 30.4 | 30.2 | 30.0 | 29.8 | 29.6 | 30.3 | 30.1 | 30.1 | 28.8 | 26.4 | 15.0 | | | | | | 18m | |
| 20m | | | 27.8 | 27.6 | 27.3 | 27.1 | 26.8 | 26.7 | 26.5 | 26.3 | 26.2 | 25.9 | 25.7 | 25.5 | 26.2 | 25.9 | 25.9 | 25.9 | 25.7 | 15.0 | 12.0 | | | | | 20m | |
| 22m | | | 24.7 | 24.4 | 24.2 | 24.0 | 23.7 | 23.5 | 23.4 | 23.1 | 23.0 | 22.8 | 22.5 | 22.3 | 22.9 | 22.6 | 22.7 | 22.6 | 22.4 | 15.0 | 12.0 | | | | | 22m | |
| 24m | | | | 21.9 | 21.6 | 21.4 | 21.1 | 20.9 | 20.8 | 20.6 | 20.4 | 20.2 | 19.9 | 19.7 | 20.2 | 20.0 | 20.0 | 20.0 | 19.7 | 15.0 | 12.0 | 8.0 | 8.0 | 8.0 | 8.0 | 24m | |
| 26m | | | | | 19.5 | 19.3 | 19.0 | 18.8 | 18.7 | 18.4 | 18.2 | 18.0 | 17.7 | 17.6 | 18.0 | 17.8 | 17.8 | 17.7 | 17.5 | 15.0 | 12.0 | 8.0 | 8.0 | 8.0 | 8.0 | 26m | |
| 28m | | | | | | 17.5 | 17.2 | 17.0 | 16.9 | 16.6 | 16.4 | 16.2 | 15.9 | 15.8 | 16.2 | 15.9 | 15.9 | 15.9 | 15.6 | 15.0 | 12.0 | 8.0 | 8.0 | 8.0 | 8.0 | 28m | |
| 30m | | | | | | 16.1 | 15.7 | 15.5 | 15.4 | 15.1 | 14.9 | 14.7 | 14.4 | 14.3 | 14.6 | 14.3 | 14.3 | 14.3 | 14.0 | 14.3 | 12.0 | 8.0 | 8.0 | 8.0 | 8.0 | 30m | |
| 32m | | | | | | | 14.4 | 14.2 | 14.0 | 13.8 | 13.6 | 13.4 | 13.1 | 12.9 | 13.2 | 13.0 | 13.0 | 12.9 | 12.6 | 13.0 | 12.0 | 8.0 | 8.0 | 8.0 | 8.0 | 32m | |
| 34m | | | | | | | | 13.1 | 12.9 | 12.7 | 12.5 | 12.2 | 11.9 | 11.8 | 12.0 | 11.8 | 11.8 | 11.7 | 11.4 | 11.8 | 11.8 | 7.8 | 7.8 | 8.0 | 8.0 | 34m | |
| 36m | | | | | | | | | 11.9 | 11.7 | 11.5 | 11.2 | 10.9 | 10.8 | 11.0 | 10.7 | 10.7 | 10.7 | 10.4 | 10.7 | 10.7 | 7.6 | 7.7 | 7.8 | 7.8 | 36m | |
| 38m | | | | | | | | | 11.1 | 10.8 | 10.6 | 10.3 | 10.1 | 9.9 | 10.1 | 9.8 | 9.8 | 9.8 | 9.5 | 9.8 | 9.8 | 7.4 | 7.5 | 7.7 | 7.7 | 38m | |
| 40m | | | | | | | | | | 10.1 | 9.8 | 9.6 | 9.3 | 9.1 | 9.3 | 9.0 | 9.0 | 8.9 | 8.6 | 9.0 | 9.0 | 7.2 | 7.4 | 7.5 | 7.5 | 40m | |
| 42m | | | | | | | | | | | 9.1 | 8.9 | 8.6 | 8.4 | 8.5 | 8.2 | 8.2 | 8.2 | 7.9 | 8.2 | 8.2 | 7.0 | 7.2 | 7.4 | 7.4 | 42m | |
| 44m | | | | | | | | | | | | 8.2 | 7.9 | 7.7 | 7.9 | 7.6 | 7.6 | 7.5 | 7.2 | 7.6 | 7.6 | 6.8 | 7.1 | 7.2 | 7.2 | 44m | |
| 46m | | | | | | | | | | | | | 7.7 | 7.4 | 7.2 | 7.3 | 7.0 | 7.0 | 6.9 | 6.6 | 7.0 | 7.0 | 6.6 | 6.6 | 6.6 | 46m | |
| 48m | | | | | | | | | | | | | | 6.9 | 6.6 | 6.7 | 6.4 | 6.4 | 6.4 | 6.0 | 6.4 | 6.4 | 6.4 | 6.4 | 6.0 | 48m | |
| 50m | | | | | | | | | | | | | | | 6.2 | 6.2 | 5.9 | 5.9 | 5.9 | 5.5 | 5.9 | 5.9 | 5.9 | 5.9 | 5.5 | 50m | |
| 52m | | | | | | | | | | | | | | | | 5.8 | 5.4 | 5.4 | 5.3 | 4.9 | 5.4 | 5.4 | 5.4 | 5.3 | 4.9 | 52m | |
| 54m | | | | | | | | | | | | | | | | | 5.4 | 5.0 | 5.0 | 4.8 | 4.4 | 5.0 | 5.0 | 5.0 | 4.8 | 4.4 | 54m |
| 56m | | | | | | | | | | | | | | | | | | 4.5 | 4.5 | 4.4 | 4.0 | 4.5 | 4.5 | 4.5 | 4.4 | 4.0 | 56m |
| 58m | | | | | | | | | | | | | | | | | | | 4.1 | 4.0 | 3.6 | 4.1 | 4.1 | 4.1 | 4.0 | 3.6 | 58m |
| 60m | | | | | | | | | | | | | | | | | | | | 3.6 | 3.2 | | | | 3.6 | 3.2 | 60m |
| 62m | | | | | | | | | | | | | | | | | | | | 3.2 | 2.8 | | | | 3.2 | 2.8 | 62m |
| 跨距 主臂长度 | 60' | 70' | 80' | 90' | 100' | 110' | 120' | 130' | 140' | 150' | 160' | 170' | 180' | 190' | 200' | 210' | 220' | 230' | 240' | 12m副 | 18m副 | 24m副 | 24m副 | 24m副 | 24m副 | 跨距 主臂长度 | |
| | 18m | 21m | 24m | 27m | 30m | 33m | 36m | 39m | 42m | 45m | 48m | 51m | 54m | 57m | 61m | 64m | 67m | 70m | 73m | 67m主+ | 67m主+ | 67m主+ | 70m主+ | 73m主+ | | | |

0 1

P&H 5170 履带式起重机副臂性能表

建议使用时查随车性能表

说明：暂缺少部分组件，带*号标示副臂工况不能组装

单位：吨

| 主臂长度(m) | 57.91 | | | | | | | | 60.96 | | | | | | | | 主臂长度(m) |
|---------|-------|------|-------|-----|---------|-----|---------|-----|-------|------|-------|-----|---------|-----|---------|-----|---------|
| | 12.19 | | 18.29 | | * 24.38 | | * 30.48 | | 12.19 | | 18.29 | | * 24.38 | | * 30.48 | | |
| 副臂长度(m) | 10° | 30° | 10° | 30° | 10° | 30° | 10° | 30° | 10° | 30° | 10° | 30° | 10° | 30° | 10° | 30° | 副臂偏置角 |
| 作业半径(m) | 10° | 30° | 10° | 30° | 10° | 30° | 10° | 30° | 10° | 30° | 10° | 30° | 10° | 30° | 10° | 30° | 作业半径(m) |
| 16.0 | 15.0 | | | | | | | | | | | | | | | | 16.0 |
| 18.0 | 15.0 | | | | | | | | 15.0 | | | | | | | | 18.0 |
| 20.0 | 15.0 | 13.0 | 12.0 | | | | | | 15.0 | 13.0 | 12.0 | | | | | | 20.0 |
| 22.0 | 15.0 | 13.0 | 12.0 | | 8.0 | | | | 15.0 | 13.0 | 12.0 | | 8.0 | | | | 22.0 |
| 24.0 | 15.0 | 13.0 | 12.0 | 8.0 | 8.0 | | 4.0 | | 15.0 | 13.0 | 12.0 | | 8.0 | | 4.0 | | 24.0 |
| 26.0 | 15.0 | 13.0 | 12.0 | 8.0 | 8.0 | | 4.0 | | 15.0 | 13.0 | 12.0 | 8.0 | 8.0 | | 4.0 | | 26.0 |
| 28.0 | 15.0 | 13.0 | 12.0 | 8.0 | 8.0 | 6.0 | 4.0 | | 15.0 | 13.0 | 12.0 | 8.0 | 8.0 | | 4.0 | | 28.0 |
| 30.0 | 14.3 | 13.0 | 12.0 | 8.0 | 8.0 | 6.0 | 4.0 | | 14.6 | 13.0 | 12.0 | 8.0 | 8.0 | 6.0 | 4.0 | | 30.0 |
| 32.0 | 12.9 | 12.9 | 12.0 | 8.0 | 7.8 | 6.0 | 4.0 | 3.0 | 13.2 | 13.0 | 12.0 | 8.0 | 7.8 | 6.0 | 4.0 | 3.0 | 32.0 |
| 34.0 | 11.8 | 11.8 | 11.8 | 8.0 | 7.6 | 6.0 | 4.0 | 3.0 | 12.0 | 12.0 | 12.0 | 8.0 | 7.6 | 6.0 | 4.0 | 3.0 | 34.0 |
| 36.0 | 10.8 | 10.8 | 10.8 | 8.0 | 7.4 | 6.0 | 4.0 | 3.0 | 11.0 | 11.0 | 11.0 | 8.0 | 7.5 | 6.0 | 4.0 | 3.0 | 36.0 |
| 38.0 | 9.9 | 9.9 | 9.9 | 8.0 | 7.2 | 6.0 | 4.0 | 3.0 | 10.1 | 10.1 | 10.1 | 8.0 | 7.3 | 6.0 | 4.0 | 3.0 | 38.0 |
| 40.0 | 9.1 | 9.1 | 9.1 | 8.0 | 7.0 | 5.9 | 4.0 | 3.0 | 9.3 | 9.3 | 9.3 | 8.0 | 7.1 | 5.9 | 4.0 | 3.0 | 40.0 |
| 42.0 | 8.4 | 8.4 | 8.4 | 7.7 | 6.8 | 5.7 | 3.9 | 3.0 | 8.5 | 8.5 | 8.5 | 8.0 | 6.9 | 5.8 | 3.9 | 3.0 | 42.0 |
| 44.0 | 7.7 | 7.7 | 7.7 | 7.5 | 6.6 | 5.6 | 3.7 | 3.0 | 7.9 | 7.9 | 7.9 | 7.9 | 6.7 | 5.7 | 3.8 | 3.0 | 44.0 |
| 46.0 | 7.2 | 7.2 | 7.2 | 7.2 | 6.4 | 5.4 | 3.6 | 2.9 | 7.3 | 7.3 | 7.3 | 7.3 | 6.6 | 5.6 | 3.7 | 2.9 | 46.0 |
| 48.0 | 6.6 | 6.6 | 6.6 | 6.6 | 6.2 | 5.3 | 3.4 | 2.9 | 6.7 | 6.7 | 6.7 | 6.7 | 6.4 | 5.4 | 3.5 | 2.9 | 48.0 |
| 50.0 | 6.2 | 6.2 | 6.2 | 6.2 | 6.0 | 5.1 | 3.3 | 2.8 | 6.2 | 6.2 | 6.2 | 6.2 | 6.2 | 5.3 | 3.4 | 2.8 | 50.0 |
| 52.0 | | | | | | | | | 5.8 | 5.8 | 5.8 | 5.8 | 5.8 | 5.2 | 3.3 | 2.8 | 52.0 |
| 54.0 | | | | | | | | | 5.4 | 5.4 | 5.4 | 5.4 | 5.4 | 5.1 | 3.2 | 2.7 | 54.0 |

P&H 5170 履带式起重机副臂性能表

建议使用时查随车性能表

说明：暂缺少部分组件，带*号标示副臂工况不能组装

单位：吨

| 主臂长度(m) | 64.01 | | | | | | | | 67.06 | | | | | | | | 主臂长度(m) |
|------------------|-------|------|-------|-----|---------|-----|---------|-----|-------|------|-------|-----|---------|-----|---------|-----|------------------|
| 副臂长度(m) | 12.19 | | 18.29 | | * 24.38 | | * 30.48 | | 12.19 | | 18.29 | | * 24.38 | | * 30.48 | | 副臂长度(m) |
| 副臂偏置角 作业半径(m) | 10° | 30° | 10° | 30° | 10° | 30° | 10° | 30° | 10° | 30° | 10° | 30° | 10° | 30° | 10° | 30° | 副臂偏置角 作业半径(m) |
| 18.0 | 15.0 | | | | | | | | 15.0 | | | | | | | | 18.0 |
| 20.0 | 15.0 | | 12.0 | | | | | | 15.0 | | 12.0 | | | | | | 20.0 |
| 22.0 | 15.0 | 13.0 | 12.0 | | 8.0 | | | | 15.0 | 13.0 | 12.0 | | | | | | 22.0 |
| 24.0 | 15.0 | 13.0 | 12.0 | | 8.0 | | 4.0 | | 15.0 | 13.0 | 12.0 | | 8.0 | | 4.0 | | 24.0 |
| 26.0 | 15.0 | 13.0 | 12.0 | 8.0 | 8.0 | | 4.0 | | 15.0 | 13.0 | 12.0 | 8.0 | 8.0 | | 4.0 | | 26.0 |
| 28.0 | 15.0 | 13.0 | 12.0 | 8.0 | 8.0 | | 4.0 | | 15.0 | 13.0 | 12.0 | 8.0 | 8.0 | | 4.0 | | 28.0 |
| 30.0 | 14.3 | 13.0 | 12.0 | 8.0 | 8.0 | 6.0 | 4.0 | | 14.3 | 13.0 | 12.0 | 8.0 | 8.0 | 6.0 | 4.0 | | 30.0 |
| 32.0 | 13.0 | 13.0 | 12.0 | 8.0 | 8.0 | 6.0 | 4.0 | | 13.0 | 13.0 | 12.0 | 8.0 | 8.0 | 6.0 | 4.0 | | 32.0 |
| 34.0 | 11.8 | 11.8 | 11.8 | 8.0 | 7.8 | 6.0 | 4.0 | 3.0 | 11.8 | 11.8 | 11.8 | 8.0 | 7.8 | 6.0 | 4.0 | 3.0 | 34.0 |
| 36.0 | 10.7 | 10.7 | 10.7 | 8.0 | 7.6 | 6.0 | 4.0 | 3.0 | 10.7 | 10.7 | 10.7 | 8.0 | 7.6 | 6.0 | 4.0 | 3.0 | 36.0 |
| 38.0 | 9.8 | 9.8 | 9.8 | 8.0 | 7.4 | 6.0 | 4.0 | 3.0 | 9.8 | 9.8 | 9.8 | 8.0 | 7.4 | 6.0 | 4.0 | 3.0 | 38.0 |
| 40.0 | 9.0 | 9.0 | 9.0 | 8.0 | 7.2 | 6.0 | 4.0 | 3.0 | 9.0 | 9.0 | 9.0 | 8.0 | 7.2 | 6.0 | 4.0 | 3.0 | 40.0 |
| 42.0 | 8.2 | 8.2 | 8.2 | 8.0 | 7.0 | 5.9 | 4.0 | 3.0 | 8.2 | 8.2 | 8.2 | 8.0 | 7.0 | 5.9 | 4.0 | 3.0 | 42.0 |
| 44.0 | 7.6 | 7.6 | 7.6 | 7.6 | 6.8 | 5.7 | 3.9 | 3.0 | 7.6 | 7.6 | 7.6 | 7.6 | 6.8 | 5.7 | 3.9 | 3.0 | 44.0 |
| 46.0 | 7.0 | 7.0 | 7.0 | 7.0 | 6.6 | 5.6 | 3.8 | 3.0 | 7.0 | 7.0 | 7.0 | 7.0 | 6.6 | 5.6 | 3.8 | 3.0 | 46.0 |
| 48.0 | 6.4 | 6.4 | 6.4 | 6.4 | 6.4 | 5.4 | 3.7 | 2.9 | 6.4 | 6.4 | 6.4 | 6.4 | 6.4 | 5.4 | 3.7 | 3.0 | 48.0 |
| 50.0 | 5.9 | 5.9 | 5.9 | 5.9 | 5.9 | 5.3 | 3.6 | 2.9 | 5.9 | 5.9 | 5.9 | 5.9 | 5.9 | 5.3 | 3.6 | 2.9 | 50.0 |
| 52.0 | 5.4 | 5.4 | 5.4 | 5.4 | 5.4 | 5.1 | 3.5 | 2.8 | 5.4 | 5.4 | 5.4 | 5.4 | 5.4 | 5.1 | 3.5 | 2.8 | 52.0 |
| 54.0 | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | 3.4 | 2.8 | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | 5.0 | 3.4 | 2.8 | 54.0 |
| 56.0 | 4.5 | 4.5 | 4.5 | 4.5 | 4.5 | 4.5 | 3.3 | 2.7 | 4.5 | 4.5 | 4.5 | 4.5 | 4.5 | 4.5 | 3.3 | 2.7 | 56.0 |
| 58.0 | | | | | | | | | 4.1 | 4.1 | 4.1 | 4.1 | 4.1 | 4.1 | 3.2 | 2.6 | 58.0 |

P&H 5170 履带式起重机副臂性能表

建议使用时查随车性能表

说明：暂缺少部分组件，带*号标示副臂工况不能组装

单位：吨

| 主臂长度(m) | 70.10 | | | | | | | | 73.15 | | | | | | | | 主臂长度(m) |
|------------------|-------|------|-------|-----|---------|-----|---------|-----|-------|------|-------|-----|---------|-----|---------|-----|------------------|
| | 12.19 | | 18.29 | | * 24.38 | | * 30.48 | | 12.19 | | 18.29 | | * 24.38 | | * 30.48 | | |
| 副臂偏置角 作业半径(m) | 10° | 30° | 10° | 30° | 10° | 30° | 10° | 30° | 10° | 30° | 10° | 30° | 10° | 30° | 10° | 30° | 副臂偏置角 作业半径(m) |
| 18.0 | 15.0 | | | | | | | | 15.0 | | | | | | | | 18.0 |
| 20.0 | 15.0 | | | | | | | | 15.0 | | | | | | | | 20.0 |
| 22.0 | 15.0 | 13.0 | 12.0 | | | | | | 15.0 | 13.0 | 12.0 | | | | | | 22.0 |
| 24.0 | 15.0 | 13.0 | 12.0 | | 8.0 | | | | 15.0 | 13.0 | 12.0 | | 8.0 | | | | 24.0 |
| 26.0 | 15.0 | 13.0 | 12.0 | 8.0 | 8.0 | | 4.0 | | 15.0 | 13.0 | 12.0 | | 8.0 | | 4.0 | | 26.0 |
| 28.0 | 15.0 | 13.0 | 12.0 | 8.0 | 8.0 | | 4.0 | | 15.0 | 13.0 | 12.0 | 8.0 | 8.0 | | 4.0 | | 28.0 |
| 30.0 | 14.3 | 13.0 | 12.0 | 8.0 | 8.0 | 6.0 | 4.0 | | 14.0 | 13.0 | 12.0 | 8.0 | 8.0 | | 4.0 | | 30.0 |
| 32.0 | 12.9 | 12.9 | 12.0 | 8.0 | 8.0 | 6.0 | 4.0 | | 12.6 | 12.6 | 12.0 | 8.0 | 8.0 | 6.0 | 4.0 | | 32.0 |
| 34.0 | 11.7 | 11.7 | 11.7 | 8.0 | 7.8 | 6.0 | 4.0 | 3.0 | 11.4 | 11.4 | 11.4 | 8.0 | 8.0 | 6.0 | 4.0 | | 34.0 |
| 36.0 | 10.7 | 10.7 | 10.7 | 8.0 | 7.7 | 6.0 | 4.0 | 3.0 | 10.4 | 10.4 | 10.4 | 8.0 | 7.8 | 6.0 | 4.0 | 3.0 | 36.0 |
| 38.0 | 9.8 | 9.8 | 9.8 | 8.0 | 7.5 | 6.0 | 4.0 | 3.0 | 9.5 | 9.5 | 9.5 | 8.0 | 7.7 | 6.0 | 4.0 | 3.0 | 38.0 |
| 40.0 | 8.9 | 8.9 | 8.9 | 8.0 | 7.4 | 6.0 | 4.0 | 3.0 | 8.6 | 8.6 | 8.6 | 8.0 | 7.5 | 6.0 | 4.0 | 3.0 | 40.0 |
| 42.0 | 8.2 | 8.2 | 8.2 | 8.0 | 7.2 | 6.0 | 4.0 | 3.0 | 7.9 | 7.9 | 7.9 | 7.8 | 7.4 | 6.0 | 4.0 | 3.0 | 42.0 |
| 44.0 | 7.5 | 7.5 | 7.5 | 7.5 | 7.1 | 5.8 | 4.0 | 3.0 | 7.2 | 7.2 | 7.2 | 7.2 | 7.2 | 5.8 | 4.0 | 3.0 | 44.0 |
| 46.0 | 6.9 | 6.9 | 6.9 | 6.9 | 6.9 | 5.6 | 3.9 | 3.0 | 6.6 | 6.6 | 6.6 | 6.6 | 6.6 | 5.6 | 4.0 | 3.0 | 46.0 |
| 48.0 | 6.4 | 6.4 | 6.4 | 6.4 | 6.4 | 5.4 | 3.8 | 3.0 | 6.0 | 6.0 | 6.0 | 6.0 | 6.0 | 5.3 | 3.9 | 3.0 | 48.0 |
| 50.0 | 5.9 | 5.9 | 5.9 | 5.9 | 5.9 | 5.2 | 3.7 | 3.0 | 5.5 | 5.5 | 5.5 | 5.5 | 5.5 | 5.1 | 3.7 | 3.0 | 50.0 |
| 52.0 | 5.3 | 5.3 | 5.3 | 5.3 | 5.3 | 5.0 | 3.6 | 2.9 | 4.9 | 4.9 | 4.9 | 4.9 | 4.9 | 4.9 | 3.6 | 2.9 | 52.0 |
| 54.0 | 4.8 | 4.8 | 4.8 | 4.8 | 4.8 | 4.8 | 3.4 | 2.8 | 4.4 | 4.4 | 4.4 | 4.4 | 4.4 | 4.4 | 3.5 | 2.8 | 54.0 |
| 56.0 | 4.4 | 4.4 | 4.4 | 4.4 | 4.4 | 4.4 | 3.3 | 2.8 | 4.0 | 4.0 | 4.0 | 4.0 | 4.0 | 4.0 | 3.4 | 2.8 | 56.0 |
| 58.0 | 4.0 | 4.0 | 4.0 | 4.0 | 4.0 | 4.0 | 3.2 | 2.7 | 3.6 | 3.6 | 3.6 | 3.6 | 3.6 | 3.6 | 3.2 | 2.7 | 58.0 |
| 60.0 | 3.6 | 3.6 | 3.6 | 3.6 | 3.6 | 3.6 | 3.1 | 2.6 | 3.2 | 3.2 | 3.2 | 3.2 | 3.2 | 3.2 | 3.1 | 2.6 | 60.0 |
| 62.0 | 3.2 | 3.2 | 3.2 | 3.2 | 3.2 | 3.2 | 3.0 | 2.5 | 2.8 | 2.8 | 2.8 | 2.8 | 2.8 | 2.8 | 2.8 | 2.5 | 62.0 |