

P&H 5250 履带式起重机主臂性能表

建议使用时查随车性能表

4块配重 单位：吨

主臂长度 跨距	24m 80'	27m 90'	30m 100'	33m 110'	36m 120'	39m 130'	42m 140'	45m 150'	48m 160'	51m 170'	54m 180'	57m 190'	61m 200'	64m 210'	67m 220'	70m 230'	73m 240'	76m 250'	79m 260'	82m 270'	85m 280'	88m 290'	主臂长度 跨距			
5.8m	226.7																							5.8m		
6.0m	226.7																								6.0m	
6.2m	226.7	226.7																							6.2m	
6.5m	226.7	226.4	219.3																						6.5m	
6.9m	226.7	224.3	216.8	209.5																					6.9m	
7.0m	226.7	224.3	216.8	209.5																					7.0m	
7.3m	203.4	203.4	203.2	198.0	198.0																				7.3m	
7.5m	203.4	203.4	203.2	197.3	191.3	133.5																			7.5m	
8.0m	182.1	182.0	181.9	181.7	177.2	172.1	158.6																		8.0m	
8.3m	164.8	164.7	164.5	164.4	164.2	160.3	156.5	152.5																	8.3m	
8.5m	164.8	164.7	164.5	164.4	164.2	160.3	156.5	152.0	137.3																8.5m	
9.0m	150.4	150.3	150.2	150.0	149.8	149.7	146.7	143.1	136.6	130.5															9.0m	
9.4m	138.2	138.1	138.0	137.8	137.7	137.5	137.4	134.6	132.0	129.4	124.6														9.4m	
9.5m	138.2	138.1	138.0	137.8	137.7	137.5	137.4	134.6	132.0	129.1	124.5	119.4													9.5m	
10.0m	127.8	127.7	127.6	127.4	127.3	127.1	127.0	126.8	124.2	121.5	119.0	117.4	105.8												10.0m	
10.4m	111.0	110.9	110.8	110.6	110.5	110.3	110.2	110.0	109.8	109.2	107.0	104.8	103.1	98.9											10.4m	
11.0m	111.0	110.9	110.8	110.6	110.5	110.3	110.2	110.0	109.8	109.2	107.0	104.8	103.1	97.4	92.8	85.0									11.0m	
11.5m	98.1	97.9	97.8	97.6	97.5	97.3	97.2	97.0	96.8	96.6	96.5	95.3	93.7	91.9	90.4	84.5	73.5								11.5m	
12m	98.1	97.9	97.8	97.6	97.5	97.3	97.2	97.0	96.8	96.6	96.5	95.3	93.7	91.9	90.4	84.5	73.3	66.5	61.4						12m	
13m	87.7	87.5	87.4	87.2	87.1	86.9	86.8	86.6	86.4	86.2	86.1	85.9	85.5	84.0	83.0	81.4	72.7	66.0	61.0	58.0	49.2	45.3			13m	
14m	79.2	79.0	79.0	78.8	78.6	78.4	78.4	78.2	78.0	77.7	77.7	77.4	77.2	77.0	76.1	74.6	72.2	65.5	60.5	55.8	48.8	45.0			14m	
15m	72.1	71.9	71.8	71.6	71.6	71.4	71.4	71.1	71.0	70.7	70.6	70.4	70.2	70.0	69.9	68.8	67.7	65.0	60.0	55.4	48.4	44.6			15m	
16m	66.2	66.0	65.9	65.7	65.6	65.3	65.3	65.1	64.9	64.7	64.6	64.4	64.2	63.9	63.8	63.6	63.4	62.3	59.6	54.9	48.0	44.3			16m	
17m	61.1	60.9	60.8	60.6	60.5	60.3	60.3	60.0	59.9	59.6	59.6	59.3	59.1	58.9	58.8	58.6	58.4	58.0	57.0	54.5	47.7	43.9			17m	
18m	56.6	56.5	56.4	56.2	56.0	55.8	55.8	55.6	55.4	55.2	55.1	54.9	54.7	54.4	54.3	54.1	53.9	53.6	53.2	52.1	47.3	43.5			18m	
19m	52.8	52.6	52.6	52.4	52.2	52.0	52.0	51.8	51.6	51.4	51.3	51.1	50.9	50.7	50.6	50.3	50.1	49.9	49.8	49.5	46.9	43.2			19m	
20m		49.2	49.1	48.9	48.8	48.6	48.6	48.3	48.2	47.9	47.9	47.6	47.4	47.2	47.1	46.9	46.7	46.4	46.3	46.1	45.9	42.8			20m	
22m			43.4	43.2	43.1	42.9	42.9	42.7	42.5	42.2	42.2	42.0	41.8	41.5	41.4	41.2	41.0	40.8	40.7	40.4	40.2	39.9			22m	
24m					38.4	38.2	38.2	38.0	37.8	37.5	37.5	37.3	37.1	36.8	36.7	36.5	36.3	36.1	35.9	35.7	35.5	35.5			24m	
26m						34.4	34.4	34.2	34.0	33.8	33.8	33.5	33.3	33.4	33.0	32.8	32.6	32.3	32.2	32.0	31.8	31.6			26m	
28m							31.2	31.0	30.8	30.5	30.5	30.3	30.1	29.8	29.8	29.5	29.3	29.1	29.0	28.7	28.5	28.3			28m	
30m								28.0	27.8	27.7	27.5	27.3	27.1	27.0	26.7	26.6	26.5	26.4	26.2	26.0	25.7				30m	
34m										23.4	23.4	23.2	23.0	22.7	22.7	22.4	22.1	22.2	21.9	21.7	21.5	21.2			34m	
38m												19.7	19.5	19.3	19.2	19.0	18.8	18.5	18.4	18.2	18.0	17.8			38m	
42m													16.9	16.7	16.6	16.4	16.2	16.0	15.9	15.6	15.5	15.2			42m	
46m																14.2	14.0	13.7	13.7	13.4	13.2	13.0			46m	
50m																			11.8	11.6	11.4	11.1			50m	
54m																									9.5	54m
跨距 主臂长度	24m 80'	27m 90'	30m 100'	33m 110'	36m 120'	39m 130'	42m 140'	45m 150'	48m 160'	51m 170'	54m 180'	57m 190'	61m 200'	64m 210'	67m 220'	70m 230'	73m 240'	76m 250'	79m 260'	82m 270'	85m 280'	88m 290'	主臂长度 跨距			

P&H 5250 履带式起重机副臂性能表

建议使用时查随车性能表

4块配重 单位：吨

主臂长度(m)	60,96														
副臂长度(m)	12.19			15.24			18.29			21.34			24.38		
副臂偏置角 作业半径(m)	5°	15°	25°	5°	15°	25°	5°	15°	25°	5°	15°	25°	5°	15°	25°
13	61.70														
14	55.15	52/14.8m		52.70											
15	49.90	50.95		50.05			45.60								
16	45.30	46.30	44.55/16.7m	45.45			45.50				36.10				
17	41.55	42.45	43.35	41.70	42.80		41.95				35.95			28.80	
18	38.10	38.95	39.85	38.25	39.30		38.50	39.70			35.95			28.80	
19	35.35	35.95	36.75	35.45	36.25	37.20	35.50	36.65			35.60	35.65		28.75	
20	32.70	33.45	34.20	32.85	33.75	34.65	33.10	34.10			33.15	34.35		28.75	
22	28.30	28.95	29.60	28.40	29.20	30.00	28.60	29.55	30.50		28.70	29.75	30.85	28.75	28.30
24	24.90	25.50	26.05	25.00	25.70	26.45	25.20	26.05	26.70		25.30	26.25	27.00	25.65	26.70 27.55
26	21.95	22.45	23.00	22.05	22.70	23.35	22.25	23.00	23.75		22.35	23.20	24.05	22.65	23.60 24.55
28	19.45	19.95	20.40	19.60	20.15	20.70	19.75	20.45	21.15		19.85	20.60	21.40	20.10	21.00 21.85
30	17.55	17.80	18.20	17.65	18.00	18.50	17.65	18.25	18.90		17.70	18.40	19.15	18.00	18.80 19.60
34	14.15	14.50	14.85	14.25	14.70	15.10	14.40	14.95	15.45		14.45	15.10	15.70	14.75	15.40 16.10
38	11.55	11.85	12.10	11.60	12.00	12.35	11.80	12.20	12.65		11.85	12.35	12.85	12.10	12.65 13.25
42	9.45	9.70	9.95	9.50	9.85	10.15	9.70	10.05	10.45		9.70	10.15	10.60	9.95	10.50 11.00
46	7.90	8.10	8.30	8.00	8.25	8.50	8.15	8.50	8.75		8.20	8.60	8.80	8.45	8.75 9.15
50	6.50	6.65	6.85	6.55	6.80	7.00	6.70	7.00	7.30		6.75	7.10	7.45	7.00	7.40 7.80
54	5.30	5.45	5.55	5.35	5.55	5.75	5.55	5.75	6.00		5.55	5.85	6.15	5.80	6.15 6.45
58	4.25	4.40		4.35	4.50	4.65	4.50	4.70	4.90		4.55	4.80	5.05	4.75	5.05 5.35
62	3.35	3.45		3.45	3.60		3.60	3.80	3.90		3.65	3.85	4.05	3.85	4.10 4.35
66	2.60			2.65	2.75		2.80	2.95			2.85	3.05	3.20	3.10	3.30 3.50
70															2.55

P&H 5250 履带式起重机副臂性能表

建议使用时查随车性能表

单位:吨

主臂长度(m)	64.01															
副臂长度(m)	12.19			15.24			18.29			21.34			24.38			
副臂偏置角 作业半径(m)	5°	15°	25°	5°	15°	25°	5°	15°	25°	5°	15°	25°	5°	15°	25°	
13.3	59.35															
14	54.90															
15	49.65	49.8/15.2m		49.85												
16	45.05	46.10		45.20			42.10				34.35					
17	41.30	42.25	42.85/17.1m	41.45	42.60		41.70				34.15					
18	37.90	38.80	39.65	38.05	39.10		38.30	39.55			34.15			27.85		
19	35.10	36.75	36.55	35.25	36.05	37.05	35.50	36.45			34.10			27.80		
20	32.45	33.25	34.05	32.60	33.55	34.50	32.85	33.95			32.95	33.95		27.80		
22	28.05	28.70	29.40	28.15	29.00	29.85	28.40	29.35	30.35		28.45	29.60		27.80	26.60	
24	24.65	25.25	25.85	24.80	25.50	26.25	25.00	25.85	26.60		25.05	26.10	26.85	25.40	26.50	
26	21.70	22.25	22.80	21.80	22.45	23.15	22.00	22.80	23.60		22.10	23.00	23.90	22.40	23.40	24.45
28	19.20	19.70	20.20	19.35	19.90	20.55	19.50	20.25	20.95		19.60	20.40	21.25	19.90	20.80	21.75
30	17.30	17.75	18.00	17.40	17.75	18.30	17.60	18.05	18.70		17.60	18.20	18.95	17.75	18.60	19.45
34	13.90	14.25	14.65	14.00	14.45	14.90	14.15	14.70	15.25		14.20	14.85	15.50	14.50	15.20	15.95
38	11.25	11.60	11.90	11.35	11.75	12.10	11.55	12.00	12.45		11.55	12.10	12.65	11.85	12.45	13.05
42	9.15	9.45	9.70	9.25	9.60	9.90	9.40	9.85	10.20		9.45	9.95	10.40	9.70	10.25	10.80
46	7.65	7.85	8.10	7.70	8.00	8.30	7.90	8.25	8.60		7.95	8.35	8.75	8.20	8.65	8.90
50	6.20	6.40	6.60	6.30	6.55	6.80	6.45	6.80	7.05		6.50	6.85	7.20	6.75	7.15	7.55
54	5.05	5.20	5.35	5.10	5.30	5.50	5.25	5.55	5.80		5.30	5.60	5.90	5.55	5.90	6.25
58	4.00	4.15	4.25	4.10	4.25	4.40	4.25	4.45	4.65		4.30	4.55	4.80	4.50	4.85	5.10
62	3.10	3.20		3.20	3.35	3.45	3.35	3.55	3.70		3.35	3.60	3.85	3.60	3.90	4.15
66								2.70				2.80	2.95	2.85	3.05	3.30

1
1
3
1

P&H 5250 履带式起重机副臂性能表

建议使用时查随车性能表

单位:吨

主臂长度(m)	67,06														
副臂长度(m)	12.19			15.24			18.29			21.34			24.38		
副臂偏置角 作业半径(m)	5°	15°	25°	5°	15°	25°	5°	15°	25°	5°	15°	25°	5°	15°	25°
13.7	53.80														
14	53.80														
15	49.50	47.75/15.6m		45.95											
16	44.90	45.95		45.05			38.90								
17	41.15	42.15	41.65/17.4m	41.30	42.50		38.75			33.00					
18	37.75	38.65	39.55	37.90	39.00		38.15			32.90			26.35		
19	34.95	35.60	36.45	35.10	35.90		35.35	36.35		32.90			26.35		
20	32.35	33.10	33.90	32.45	33.40	34.40	32.70	33.85		32.80	32.40		26.30		
22	27.90	28.60	29.30	28.05	28.85	29.70	28.25	29.25	30.25	28.35	29.45		26.30	25.85	
24	24.55	25.15	25.80	24.65	25.40	26.15	24.85	25.75	26.65	24.95	25.95	26.75	25.30	25.85	
26	21.60	22.15	22.70	21.65	22.35	23.05	21.90	22.70	23.50	21.95	22.85	23.80	22.30	23.30	24.35
28	19.10	19.60	20.10	19.20	19.80	20.40	19.40	20.10	20.85	19.45	20.30	21.10	19.75	20.70	21.65
30	17.20	17.65	17.90	17.30	17.65	18.20	17.45	17.90	18.60	17.55	18.10	18.85	17.60	18.45	19.35
34	13.75	14.15	14.55	13.85	14.35	14.80	14.05	14.60	15.15	14.10	14.75	15.40	14.35	15.10	15.85
38	11.15	11.45	11.80	11.20	11.65	12.05	11.40	11.90	12.35	11.45	12.00	12.55	11.70	12.35	12.95
42	9.05	9.35	9.60	9.15	9.50	9.85	9.30	9.70	10.10	9.35	9.85	10.30	9.60	10.15	10.70
46	7.55	7.80	8.00	7.60	7.90	8.20	7.80	8.15	8.50	7.85	8.25	8.65	8.10	8.55	8.85
50	6.10	6.35	6.50	6.20	6.45	6.70	6.35	6.65	6.95	6.40	6.75	7.10	6.65	7.05	7.45
54	4.95	5.10	5.25	5.00	5.20	5.40	5.15	5.40	5.70	5.20	5.50	5.85	5.40	5.80	6.15
58	3.90	4.05	4.15	3.95	4.15	4.35	4.10	4.35	4.60	4.15	4.45	4.70	4.40	4.70	5.05
62	3.00	3.15	3.25	3.10	3.25	3.40	3.20	3.45	3.60	3.25	3.50	3.75	3.50	3.80	4.05
66									2.80			2.90	2.70	2.95	3.20

1
1
4
1

P&H 5250 履带式起重机副臂性能表

建议使用时查随车性能表

单位:吨

主臂长度(m)	70,10								
副臂长度(m)	12.19			15.24			18.29		
副臂偏置角 作业半径(m)	5°	15°	25°	5°	15°	25°	5°	15°	25°
14	48.60								
15	48.60	46.2/15.9m		42.20					
16	44.70	45.80		42.20			36.60		
17	40.95	41.95	40.1/17.8m	41.10			36.45		
18	37.55	38.45	39.40	37.65	38.80		35.35		
19	34.75	35.60	36.30	34.90	35.75		35.15	35.35	
20	32.10	32.90	33.75	32.25	33.25	34.25	32.50	33.65	
22	27.65	28.40	29.10	27.80	28.65	29.55	28.00	29.05	30.10
24	24.30	24.95	25.60	24.40	25.20	26.00	24.60	25.55	26.50
26	21.35	21.90	22.50	21.45	22.15	22.85	21.65	22.50	23.35
28	18.85	19.35	19.90	18.95	19.60	20.25	19.15	19.90	20.65
30	16.95	17.40	17.70	17.05	17.60	18.00	17.25	17.70	18.40
34	13.50	13.95	14.35	13.60	14.10	14.60	13.80	14.40	14.95
38	10.90	11.25	11.60	10.95	11.40	11.80	11.15	11.65	12.15
42	8.80	9.10	9.40	8.85	9.25	9.60	9.05	9.50	9.90
46	7.30	7.55	7.80	7.35	7.70	8.00	7.55	7.90	8.30
50	5.85	6.10	6.30	5.95	6.20	6.45	6.10	6.45	6.75
54	4.65	4.85	5.05	4.75	4.95	5.20	4.90	5.20	5.45
58	3.65	3.80	3.95	3.70	3.90	4.10	3.85	4.10	4.35
62		2.90	3.00	2.85	3.00	3.15	2.95	3.20	3.40